

## HDBaseT Extender

### Stoltzen SHE630 HDBaseT™ Rx HDBT Reciever for SHE630WP Wallplate

Product number: SHE630-RX



## Product Description

The Stoltzen SHE630-RX Receiver is designed to work with the SHE630WP-TX Wallplate Transmitter, receiving HDMI high-definition signal, bidirectional IR control signal, bidirectional RS-232 control signal, and USB 2.0 signal over CAT6 up to 328ft/100m (HBT mode) or 492ft/150m (LRM mode). Video resolution is up to 4K2K@60Hz (4:4:4). It supports POC function with POC control switch, allowing for power to be supplied through the same cable that transmits the data.

If in LRM-Mode USB transferspeed is lower.

## Main Specifications

<b>Brand</b>	Stoltzen
<b>Color</b>	Black
<b>HDMI version</b>	HDMI 2.0b
<b>HDCP supported</b>	2.2, 1.4
<b>Max Input Resolution</b>	3840x2160 60Hz
<b>Max Resolution Output</b>	3840x2160 60Hz
<b>CEC</b>	Passthrough
<b>Color depth</b>	8-bit, 10-bit, 12-bit
<b>Bandwidth</b>	18Gbps
<b>Inputs</b>	1 x HDBT (RJ45) 1 x IR (3pin-3.81mm Phoenix connector) 1 x SERVICE (Micro USB) 1 x RS-232 (3pin-3.81mm Phoenix connector)



---

<b>Outputs</b>	1 x HDMI (Type A, 19-pin female) 1 x AUDIO (3pin-3.81mm Phoenix connector) 2 x USB 2.0 (USB Type A) 1 x RS-232 (3pin-3.81mm Phoenix connector) 1 x IR (2pin-3.81mm Phoenix connector)
----------------	---

---

## **Extended Specifications**

---

<b>Distance 4K (m)</b>	100
<b>Distance 2K (m)</b>	100
<b>EAN</b>	7072262010281
<b>Certifications</b>	CE, REACH

---

